

Cisco 2500 Series Wireless Controllers

Small to Medium-Sized Enterprise and Branch Office Controller

- Support for up to 50 access points and 500 clients.
- 802.11n ready support up to 500 Mbps.
- Payment Card Industry (PCI) support enables certification for scanner and kiosk deployments.

Licensing Flexibility and Investment Protection

- Additional access point licenses may be added over time.

Comprehensive Security

- Full Control and Provisioning of Wireless Access Points (CAPWAP) access point to controller encryption.
- Supports rogue access point detection and detection of denial-of-service attacks.
- Management frame protection detects malicious users and alerts network administrators.

Cisco CleanAir™ technology

- Detects, classifies, locates, and mitigates RF interference to provide performance protection for 802.11n networks.

Cisco OfficeExtend Solution

- Secure, simple, cost-effective mobile teleworker solution.

Product Overview

The Cisco® 2500 Series [Wireless Controller](#) enables systemwide [wireless](#) functions in small to medium-sized enterprises and branch offices. Designed for [802.11n](#) performance, Cisco 2500 Series Wireless Controllers are entry-level controllers that provide real-time communication between [Cisco Aironet® access points](#) to simplify the deployment and operation of wireless networks (Figure 1).

Figure 1 Cisco 2500 Series Wireless Controller



As a component of the [Cisco Unified Wireless Network](#), this controller delivers centralized security policies, wireless intrusion prevention system (wIPS) capabilities, award-winning RF management, and quality of service (QoS) for voice and video. Delivering 802.11n performance and scalability, the Cisco 2500 Series provides low total cost of ownership and flexibility to scale as network requirements grow.

Cisco 2500 Series Wireless Controller base [access point](#) licensing offers flexibility with 5, 15, 25, or 50 [access points](#). Additional access point support may be added in increments of 5 or 25.

Table 1 lists the features and benefits of the Cisco 2500 Series Wireless Controllers.

Table 1. Cisco 2500 Series Wireless Controller Features and Benefits

Feature	Benefits
Scalability	<ul style="list-style-type: none"> • Supports 5, 15, 25, or 50 access points
High Performance	<ul style="list-style-type: none"> • Wired-network speed and nonblocking performance for 802.11n networks
RF Management	<ul style="list-style-type: none"> • Provides both real-time and historical information about RF interference impacting network performance across controllers, via systemwide Cisco CleanAir technology integration
Comprehensive End-to-End Security	<ul style="list-style-type: none"> • Offers CAPWAP-compliant Datagram Transport Layer Security (DTLS) encryption to help ensure full-line-rate encryption between access points and controllers across remote WAN/LAN links
End-to-end Voice	<ul style="list-style-type: none"> • Supports Unified Communications for improved collaboration through messaging, presence, and conferencing • Supports all Cisco Unified Communications Wireless IP Phones for cost-effective, real-time voice services
High-Performance Video	<ul style="list-style-type: none"> • Integrates Cisco VideoStream technology as part of the Cisco medianet framework to optimize the delivery of video applications across the WLAN
PCI Integration	<ul style="list-style-type: none"> • Part of Payment Card Industry (PCI) certified architecture, and are well-suited for retail customers who deploy transactional data applications such as scanners and kiosks

Feature	Benefits
OfficeExtend	<ul style="list-style-type: none"> • Supports corporate wireless service for mobile and remote workers with secure wired tunnels to the Cisco Aironet® 600, 1130, 1140 or 3500 Series Access Points • Extends the corporate network to remote locations with minimal setup and maintenance requirements • Improves productivity and collaboration at remote site locations • Separate service set identifier (SSID) tunnels allow both corporate and personal Internet access • Reduced carbon dioxide emissions from a decrease in commuting • Higher employee job satisfaction from ability to work at home • Improves business resiliency by providing continuous, secure connectivity in the event of disasters, pandemics, or inclement weather
Enterprise Wireless Mesh	<ul style="list-style-type: none"> • Allows access points to dynamically establish wireless connections without the need for a physical connection to the wired network • Available on select Cisco Aironet access points, Enterprise Wireless Mesh is ideal for warehouses, manufacturing floors, shopping centers, and any other location where extending a wired connection may prove difficult or aesthetically unappealing
Environmentally Responsible	<ul style="list-style-type: none"> • Organizations may choose to turn off access point radios to reduce power consumption during off-peak hours
Mobility, security and management for IPv6 & dual-stack clients	<ul style="list-style-type: none"> • Secure, reliable wireless connectivity and consistent end-user experience • Increased network availability by proactive blocking of known threats • Equips administrators for IPv6 troubleshooting, planning, client traceability from a common wired and wireless management system

Product Specifications

Table 2 lists the product specification for Cisco 2500 Series Wireless Controllers.

Table 2. Product Specifications for the Cisco 2500 Wireless Controller

Item	Specification
Wireless Standards	IEEE 802.11a, 802.11b, 802.11g, 802.11d, WMM/802.11e, 802.11h, 802.11n, 802.11u
Wired/Switching/Routing	IEEE 802.3 10BASE-T, IEEE 802.3u 100BASE-TX specification, 1000BASE-T, and IEEE 802.1Q VLAN tagging.
Data Request for Comments (RFCs)	<ul style="list-style-type: none"> • RFC 768 UDP • RFC 791 IP • RFC 2460 IPv6 (passthrough bridging mode only) • RFC 792 ICMP • RFC 793 TCP • RFC 826 ARP • RFC 1122 Requirements for Internet Hosts • RFC 1519 CIDR • RFC 1542 BOOTP • RFC 2131 DHCP • RFC 5415 CAPWAP Protocol Specification
Security Standards	<ul style="list-style-type: none"> • Wi-Fi Protected Access (WPA) • IEEE 802.11i (WPA2, RSN) • RFC 1321 MD5 Message-Digest Algorithm • RFC 1851 The ESP Triple DES Transform • RFC 2104 HMAC: Keyed Hashing for Message Authentication • RFC 2246 TLS Protocol Version 1.0 • RFC 2401 Security Architecture for the Internet Protocol • RFC 2403 HMAC-MD5-96 within ESP and AH • RFC 2404 HMAC-SHA-1-96 within ESP and AH • RFC 2405 ESP DES-CBC Cipher Algorithm with Explicit IV • RFC 2406 IP Encapsulating Security Payload (ESP) • RFC 2407 Interpretation for ISAKMP • RFC 2408 ISAKMP • RFC 2409 IKE • RFC 2451 ESP CBC-Mode Cipher Algorithms • RFC 3280 Internet X.509 PKI Certificate and CRL Profile

Item	Specification
	<ul style="list-style-type: none"> • RFC 3602 The AES-CBC Cipher Algorithm and Its Use with IPsec • RFC 3686 Using AES Counter Mode with IPsec ESP • RFC 4347 Datagram Transport Layer Security • RFC 4346 TLS Protocol Version 1.1
Encryption	<ul style="list-style-type: none"> • WEP and Temporal Key Integrity Protocol-Message Integrity Check (TKIP-MIC): RC4 40, 104 and 128 bits (both static and shared keys) • Advanced Encryption Standard (AES): CBC, CCM, Counter Mode with Cipher Block Chaining Message Authentication Code Protocol (CCMP) • DES: DES-CBC, 3DES • Secure Sockets Layer (SSL) and Transport Layer Security (TLS): RC4 128-bit and RSA 1024- and 2048-bit • DTLS: AES-CBC
Authentication, Authorization, and Accounting (AAA)	<ul style="list-style-type: none"> • IEEE 802.1X • RFC 2548 Microsoft Vendor-Specific RADIUS Attributes • RFC 2716 PPP EAP-TLS • RFC 2865 RADIUS Authentication • RFC 2866 RADIUS Accounting • RFC 2867 RADIUS Tunnel Accounting • RFC 3576 Dynamic Authorization Extensions to RADIUS • RFC 3579 RADIUS Support for EAP • RFC 3580 IEEE 802.1X RADIUS Guidelines • RFC 3748 Extensible Authentication Protocol • Web-based authentication • TACACS support for management users
Management	<p>SNMP v1, v2c, v3</p> <p>RFC 854 Telnet</p> <p>RFC 1155 Management Information for TCP/IP-Based Internets</p> <p>RFC 1156 MIB</p> <p>RFC 1157 SNMP</p> <p>RFC 1213 SNMP MIB II</p> <p>RFC 1350 TFTP</p> <p>RFC 1643 Ethernet MIB</p> <p>RFC 2030 SNMP</p> <p>RFC 2616 HTTP</p> <p>RFC 2665 Ethernet-Like Interface types MIB</p> <p>RFC 2674 Definitions of Managed Objects for Bridges with Traffic Classes, Multicast Filtering, and Virtual Extensions</p> <p>RFC 2819 RMON MIB</p> <p>RFC 2863 Interfaces Group MIB</p> <p>RFC 3164 Syslog</p> <p>RFC 3414 User-Based Security Model (USM) for SNMPv3</p> <p>RFC 3418 MIB for SNMP</p> <p>RFC 3636 Definitions of Managed Objects for IEEE 802.3 MAUs</p> <p>Cisco private MIBs</p>
Management Interfaces	<ul style="list-style-type: none"> • Designed for use with Cisco Wireless Control System • Web-based: HTTP/HTTPS individual device manager • Command-line interface: Telnet, SSH, serial port
Interfaces and Indicators	<ul style="list-style-type: none"> • Console port: RJ-45 connector • Network: Four 1 Gbps Ethernet (RJ-45) <p>Note: Access point directly connected to the controller is not currently supported.</p> <ul style="list-style-type: none"> • LED indicators: Link Activity (each 1 Gigabit Ethernet port), Power, Status, Alarm

Item	Specification
Physical and Environmental	Dimensions: 1.73 x 8.00 x 6.75 in. (43.9 x 203.2 x 271.5mm) Weight: 3.5 lbs (with power supply) Temperature: <ul style="list-style-type: none"> • Operating: 32 to 104 °F (0 to 40°C) • Storage: -13 to 158°F (-25 to 70°C) Humidity: <ul style="list-style-type: none"> • Operating humidity: 10 to 95 percent, noncondensing • Storage humidity: Up to 95 percent Power adapter: Input power: 100 to 240 VAC; 50/60 Hz Heat dissipation: 72 BTU/hour
Regulatory Compliance	Safety: <ul style="list-style-type: none"> • UL 60950-1, 2nd Edition • EN 60950:2005 EMI and susceptibility (Class B): <ul style="list-style-type: none"> • U.S.: FCC Part 15.107 and 15.109 • Canada: ICES-003 • Japan: VCCI • Europe: EN 55022, EN 55024

Ordering Information

Tables 3 and 4 provide ordering information for the Cisco 2500 Series Wireless Controllers. To place an order, visit the Cisco ordering website: <http://www.cisco.com/en/US/ordering/index.shtml>.

Table 3. Ordering Information for Cisco 2500 Series Wireless Controllers

Part Number	Description	Cisco SMARTnet® 8x5xNBD
AIR-CT2504-5-K9	2500 Series Wireless Controller for up to 5 Cisco access points	CON-SNT-CT255
AIR-CT2504-15-K9	2500 Series Wireless Controller for up to 15 Cisco access points	CON-SNT-CT2515
AIR-CT2504-25-K9	2500 Series Wireless Controller for up to 25 Cisco access points	CON-SNT-CT2525
AIR-CT2504-50-K9	2500 Series Wireless Controller for up to 50 Cisco access points	CON-SNT-CT2550

Table 4. Ordering Information for Cisco 2500 Series Wireless Controllers: Optional Accessories

Part Number	Product Name
AIR-CT2504-RMNT=	Cisco 2504 Wireless Controller Rack Mount Bracket
PWR-2504-AC=	Cisco 2504 Wireless Controller Spare Power Supply (not necessary with original order as 1 power supply is included)

Additive Capacity Upgrade Licenses

The following additive capacity upgrade licenses are available for the Cisco 2500 Series.

Table 5. Ordering Information for Cisco 2500 Series Wireless Controllers: Access Point Adder Licenses (e-Delivery PAKs)

Part Number	Description	Cisco SMARTnet 8x5xNBD
L-LIC-CT2504-UPG	Primary upgrade SKU: Pick any number or combination of the following options under this SKU to upgrade one or many controllers under one product authorization key	CON-SNT-LCT25UP
L-LIC-CT2504-5A	5 Access Point Adder License for Cisco 2504 Wireless Controller (e-Delivery)	CON-SNT-LCT255A
L-LIC-CT2504-25A	25 Access Point Adder License for Cisco 2504 Wireless Controller (e-Delivery)	CON-SNT-LCT2525A

Table 6. Ordering Information for Cisco 2500 Series Wireless Controllers: Access Point Adder Licenses (Paper PAKs)

Part Number	Description	Cisco SMARTnet 8x5xNBD
LIC-CT2504-UPG	Primary upgrade SKU: Pick any number or combination of the following options under this SKU to upgrade one or many controllers under one product authorization key	CON-SNT-LCT25UP
LIC-CT2504-5A	5 Access Point Adder License for Cisco 2504 Wireless Controller (Paper Certificate - U.S. Mail)	CON-SNT-LCT255A
LIC-CT2504-25A	25 Access Point Adder License for Cisco 2504 Wireless Controller (Paper Certificate - U.S. Mail)	CON-SNT-LCT2525A

Table 7 shows the optional DTLS license for Cisco 2500 Series Wireless Controllers. When customer orders the 2500 and chooses 'none selected' (DEFAULT); in the Optional Licenses TAB, data DTLS Encryption is disabled.

Datagram Transport Layer Security (DTLS) is required for all OfficeExtend deployments to encrypt the Data Plane traffic. To enable this functionality, you must obtain a \$0 DTLS license. **Customers planning to install this device physically in Russia must obtain a physical PAK in order to enable a DTLS license and should not download the license from Cisco.com.** Please consult your local government regulations to ensure that Data DTLS encryption is permitted.

The DTLS Paper PAK license is designated for customers who purchase a controller with DTLS disabled due to import restrictions but get permission to add DTLS support after initial purchase. This optional DTLS license is required for Cisco OfficeExtend deployment.

Table 7. Optional Licensing for Cisco 2500 Series Wireless Controllers (PAKs)

Part Number	Description
LIC-CT2504-UPG	Primary upgrade SKU: Pick any number or combination of the following options under this SKU to upgrade one or many controllers under one product authorization key
LIC-CT25-DTLS-K9	Cisco 2504 Controller DTLS License (Paper Certificate - US Mail)
L-LIC-CT2504-UPG	Primary upgrade SKU: Pick any number or combination of the following options under this SKU to upgrade one or many controllers under one product authorization key
L-LIC-CT25-DTLS-K9	Cisco 2504 Controller DTLS License (electronic Certificate - must not be ordered by Russian Customers)

Other customers can simply use the procedure outlined below in order to download the DTLS license from CCO.

To obtain/download a Data DTLS License:

Step 1. Browse to <http://cisco.com/go/license>

Step 2. On the Product License Registration page, choose **Licenses Not Requiring a PAK.**

Step 3. Choose **Cisco Wireless Controllers DTLS License** under Wireless.

Step 4. Complete the remaining steps to generate the license file. The license will be provided online or via email.

Step 5. Copy the license file to your TFTP server.

Step 6. Install the license by browsing to the WLC Web Administration Page:

Management --> Software Activation --> Commands --> Action: Install License

Service and Support

Realize the full business value of your wireless network and mobility services investments faster with intelligent, customized services from Cisco and our partners. Backed by deep networking expertise and a broad ecosystem of partners, Cisco professional and technical services enable you to successfully plan, build, and run your network as a powerful business platform. Our services can help you successfully deploy the Cisco Wireless Controller and integrate mobility solutions effectively to lower the total cost of ownership and secure your wireless network.

To learn more about Cisco wireless LAN service offers, visit: <http://www.cisco.com/go/wirelesslanservices>.

For More Information

For more information about Cisco wireless controllers, contact your local account representative or visit: <http://www.cisco.com/en/US/products/ps6366/index.html>.

For more information about the Cisco Unified Wireless Network framework, visit: <http://www.cisco.com/go/unifiedwireless>.



Americas Headquarters
Cisco Systems, Inc.
San Jose, CA

Asia Pacific Headquarters
Cisco Systems (USA) Pte. Ltd.
Singapore

Europe Headquarters
Cisco Systems International BV Amsterdam,
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: www.cisco.com/go/trademarks. Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)